

Motor data sheet

M2AA 71A 4


For ordering purposes within selected meps, please add , Variant Code: 209 Special winding

Definition	Data	Unit	Remarks
Product code	3GAA 072 001-**E		
Voltage code	P		
Calculation_id	GEN_3GAA072001-E_D		
Type/Frame	M2AA 71A 4		
Design	CENELEC		
Efficiency class	IE1		
Rated output P_N	0.25	kW	
Rated voltage U_N	400	V D	± 5 % (IEC 60034-1)
Rated frequency f_N	50	Hz	± 2 % (IEC 60034-1)
Rated speed n_N	1365	r/min	
Rated current I_N	0.72	A	
Starting current I_S/I_N	4		
Nominal torque T_N	1.74	Nm	
Locked rotor torque T_l/T_N	2		
Maximum torque T_b/T_N	2.1		
Efficiency - full load 100%	65.1	%	Acc. to IEC 60034-2-1
Efficiency - 75%	66	%	
Efficiency - 50%	62.7	%	
Power factor - full load 100%	0.76		
Bearing DE/NDE	6203-2Z/C3 6202-2Z/C3		
Sound pressure level L_{pA} dB	45	dB(A)	+3dB(A)
Moment of inertia $J = \frac{1}{4} GD^2$ kgm ²	0	kg-m ²	
Weight	5.2	kg	

Motor data sheet

M2AA 71A 4

Running performance chart



Motor data sheet

M2AA 71A 4

Starting performance chart information

