

# Motor data sheet

## M2AA 132M 4

Definition	Data	Unit	Remarks
Product code	3GAA 132 212-**E		
Voltage code	S		
Type/Frame	M2AA 132M 4		
Design	CENELEC		
Efficiency class	IE2		
Rated output $P_N$	5.5	kW	
Rated voltage $U_N$	230	V X	± 5 % (IEC 60034-1)
Rated frequency $f_N$	50	Hz	± 2 % (IEC 60034-1)
Rated speed $n_N$	1465	r/min	
Rated current $I_N$	19.4	A	
Starting current $I_S/I_N$	6.3		
Nominal torque $T_N$	35.8	Nm	
Locked rotor torque $T_l/T_N$	1.9		
Maximum torque $T_b/T_N$	2.6		
Efficiency - full load 100%	89	%	Acc. to IEC 60034-2-1
Efficiency - 75%	89.8	%	
Efficiency - 50%	89.1	%	
Power factor - full load 100%	0.79		
Bearing DE/NDE	6208-2Z/C3 6206-2Z/C3		
Sound pressure level $L_{pA}$ dB	66	dB(A)	+3dB(A)
Moment of inertia $J = \frac{1}{4} GD^2$ kgm <sup>2</sup>	0.04	kg-m <sup>2</sup>	
Weight	48	kg	