

Motor data sheet

M2AA 63A 2


For ordering purposes within selected meps, please add , Variant Code: 209 Special winding

Definition	Data	Unit	Remarks
Product code	3GAA 061 001-**C		
Voltage code	D		
Calculation_id	GEN_3GAA061001-C_D		
Type/Frame	M2AA 63A 2		
Design	CENELEC		
Efficiency class	IE4		
Rated output P_N	0.18	kW	
Rated voltage U_N	380	V X	± 5 % (IEC 60034-1)
Rated frequency f_N	50	Hz	± 2 % (IEC 60034-1)
Rated speed n_N	2815	r/min	
Rated current I_N	0.53	A	
Starting current I_S/I_N	3.9		
Nominal torque T_N	0.6	Nm	
Locked rotor torque T_l/T_N	2.9		
Maximum torque T_b/T_N	2.5		
Efficiency - full load 100%	75.8	%	Acc. to IEC 60034-2-1
Efficiency - 75%	72.9	%	
Efficiency - 50%	66.7	%	
Power factor - full load 100%	0.67		
Bearing DE/NDE	6202-2Z/C3 6201-2Z/C3		
Sound pressure level L_{pA} dB	54	dB(A)	+3dB(A)
Moment of inertia $J = \frac{1}{4} GD^2$ kgm ²	0	kg-m ²	
Weight	3.9	kg	

Motor data sheet

M2AA 63A 2

Running performance chart



Motor data sheet

M2AA 63A 2

Starting performance chart information

